

Weight kg

2.90

2.90

Standard

Volume m³

0.010

0.010

UNDERWATER LIGHTS FOR CONCRETE POOLS

Plastic MINI light, fast assembly



Manufactured in PA and ABS plastic materials. Without screws, bayonet system on both the faceplate and the housing. Easy to remove using the faceplate front as a key to replace the lamp. 50 W-12 V aluminised halogen lamp and 38° opening of 95 lux light beam at 4 m distance with an illuminated circle of 2.5 m. Light easy to install in a wall conduit with a solvent weld connection (code 15661). Possibility of attaching colour lenses to the faceplate. Light supplied without transformer. Available in white ABS faceplate or S.S.

Code

Standard

Packaging

4 4




White ABS faceplate S.S. faceplate	Wall conduit	33708 36646
096	Well Collidation	17.5

Metal MINI light with niche



Light with chromed brass housing and ABS plastic parts. Supplied with niche for embedding in the pool wall and with 2.5 m cable of $2 \times 1.5 \text{ mm}^2$. Without screws, bayonet system on both the faceplate and the casing. Easy to remove using the faceplate as a key to replace the lamp. 50 W-12 V aluminised halogen lamp and 38° opening of 95 lux light beam at 4 m distance with an illuminated circle of 2.5 m. Possibility of attaching colour lenses to the outside of the faceplate. Light supplied without transformer.





Code	Packaging	Weight kg	Volume m ³
33686 36643	4 4	7.22 7.22	0.022 0.022
t and the second se			

Standard Standard

Metal MINI light, quick assembly



Light with chromed brass housing and ABS plastic parts. Without screws, bayonet system on both the faceplate and the casing. Easy to remove using the faceplate as a tool to replace the lamp. Supplied with $2.5\,\mathrm{m}$ cable of $2\,\mathrm{x}\,1.5\,\mathrm{mm^2}$. 50 W-12 V aluminised halogen lamp of and 38° opening of 95 lux light beam at 4 m distance with an illuminated circle of $2.5\,\mathrm{m}$. diameter. Easy to install in a wall conduit with a plain inner solvent weld connection (code 15661). Light supplied without transformer.

Standard

Packaging

4

4

Standard

Weight kg

4.70

4.70

Standard

Volume m³ 0.022

0.022

White ABS facepla S.S. faceplate	wall conduit	33684 36641

300

