



“洛克”  
燃氣爐



HAYWARD®

“喜活”  
燃氣爐

HAYWARD



HAYWARD 泳池行業標準



型号 (model)	H400FD	H350FD	H300FD	H250FD	H200FD	H150FD
热量/小时 BTU/Hr	400,000	350,000	300,000	250,000	200,000	150,000
宽 (Width inches)	36"	33"	30"	28"	25"	21"
深度 (Depth inches)	29½"	29½"	29½"	29½"	29½"	29½"
高度 (Height inches)	24"	24"	24"	24"	24"	24"
管径 Water Connections	2" x 2½"	2" x 2½"	2" x 2½"	2" x 2½"	2" x 2½"	2" x 2½"
热交换器 (Heat Exchanger)	Cupro Nickel	Cupro Nickel	Cupro Nickel	Cupro Nickel	Cupro Nickel	Cupro Nickel
室内通风管径 Indoor Vent Pipe Diameter (in.)	8"	8"	8"	6"	6"	6"
热重量 Heater Weight (lbs.)	160	158	145	134	123	110
燃气管径 Gas Connection at Heater	¾"	¾"	¾"	¾"	¾"	¾"

ENERGYRITE

美国最大热能制造商

先进的燃烧系统

高效不锈钢燃烧器



型号 (MODEL)	制热量 (BTU)	制热量 (大卡)	空气进口	烟囱尺寸	边墙强排烟囱尺寸	运输重量 (lbs)
ERN152	150000	37500	4"	5"	4"	183
ERN202	199999	50000	4"	5"	4"	195
ERN252	250000	62500	5"	6"	5"	217
ERN302	300000	75000	5"	6"	5"	240
ERN402	399999	100000	5"	6"	5"	269

◎特征

- 可安装室内与室外
- 加热迅速，水温舒服，高效节能
- 高质量，无故障，维护简单
- 分离游泳池和水疗池控制功能
- 配备第三方遥控接口

接线板

风机

热交换器

控制系统

CPVC管

燃烧室

